

PRESSURE TANKS

2.5 Gallon



TANKS	PART #	REGULATORS	AGITATOR	DESCRIPTION
Standard	51-200	0	None	The 2.5 gallon non-ASME tank from C.A.T. is constructed of heavy gage steel. The non-agitated tanks are Teflon coated inside and out. The tank has wheels for maneuverability or optional stationary feet. All 2.5 gallon tanks come with a removeable rigid liner.
	51-201	1	None	
	51-202	2	None	
	51-203	1	Air	
	51-204	2	Air	
Bottom Outlet	51-205	0	Air	The bottom outlet 2.5 gallon non-ASME tank from C.A.T. is constructed of heavy gage steel. The tanks have a baked on coating and come with or without agitation. The tank has wheels for maneuverability or optional stationary feet. All bottom outlet tanks have a 3/4" fluid outlet w/ ball valve.
	51-210	0	None	
	51-211	1	None	
	51-212	2	None	
	51-213	1	Air	
	51-214	2	Air	
	51-215	0	Air	

Tank Inside Dimensions: Diameter = 10 1/2"
Depth = 8 3/4" 2.5 Gallon tank liners **53-231-10** (10 Pack)
Gasket **51-220**

5 Gallon

TANKS	PART #	REGULATORS	AGITATOR	DESCRIPTION
Standard	51-500	0	Hand	The 5 gallon non-ASME tank from C.A.T. is constructed of heavy gage steel. This tank comes standard with dual fluid outlets and ball valves. Also standard is a stainless steel removable inner liner. Wheels make this tank maneuverable or it may be fitted with stationary feet. Maximum working pressure is 80 psi. The tank comes with a 2" dia. fill port.
	51-501	1	Hand	
	51-502	2	Hand	
	51-503	1	Air	
	51-504	2	Air	
	51-505	0	Air	
	51-506	0	None	
	51-507	1	None	
Bottom Outlet	51-508	2	None	The bottom outlet 5 gallon non-ASME tank from C.A.T. is constructed of heavy gage steel. The tanks have a stainless liner and come with or without agitation. The tank has wheels for maneuverability or optional stationary feet. All bottom outlet tanks have a 1" female fluid outlet with ball valve.
	51-510	0	None	
	51-511	1	None	
	51-512	2	None	
	51-513	1	Air	
	51-514	2	Air	
	51-515	0	Air	

Tank Inside Dimensions: Diameter = 12 1/2"
Depth = 15 1/2" 5 Gallon tank liners **53-543-10** (10 Pack)
Gasket **51-520**

10 Gallon

TANKS	PART #	REGULATORS	AGITATOR	DESCRIPTION
Standard	51-556	0	Hand	The 10 gallon non-ASME tank from C.A.T. is constructed of heavy gage steel. This tank comes standard with dual fluid outlets and ball valves. Also standard is a stainless steel removable inner liner. Wheels make this tank maneuverable or may be fitted with stationary feet. Maximum working pressure is 80 psi. The tank comes with a fill port.
	51-557	1	Hand	
	51-558	2	Hand	
	51-553	1	Air	
	51-554	2	Air	
	51-555	0	Air	
	51-550	0	None	
	51-551	1	None	
Bottom Outlet	51-552	2	None	The bottom outlet 10 gallon non-ASME bottom outlet tank from C.A.T. is constructed of heavy gage steel. The tanks have a stainless liner and come with or without agitation. The tank has wheels for maneuverability or optional stationary feet. All bottom outlet tanks have a 3/4" fluid outlet with ball valve.
	51-560	0	None	
	51-561	1	None	
	51-562	2	None	
	51-564	1	Air	
	51-565	2	Air	
	51-563	0	Air	

Tank Inside Dimensions = Diameter = 12 1/2"
Depth = 21 1/2" 10 Gallon tank liners **53-543-10** (10 Pack)
Gasket **51-520**

Coating Atomization Technologies P.O.Box 17820 Boulder CO 80301 (888) 820-4498 Fax(303) 438-5708

www.sprayCAT.com